



KONICA MINOLTA

THE STANDARD IN MEASURING
COLOUR, LIGHT & FORM

BC-10

BC-10 BAKING CONTRAST METER

Monitor and control the color of baked, fried, smoked, and processed foods, including ingredients. Establish specifications for crust, crumb, and ingredients. Ensure consistency in product appearance.

The food industry is a highly competitive business with production becoming a more exacting science. Consumers want their products to have a consistent appearance from purchase to purchase, and the color of your products will directly affect the sale of those products. Designed for contact measurements, Konica Minolta's BC-10 provides reliable, precise color measurements through all stages of food production. The BC-10 is not affected by lighting conditions, and eliminates inconsistencies and obstacles such as "human eye" subjectivity.

- **Production Control** - Controls specifications of crust color, crumb color, and related formulation adjustments. Simplifies co-packing procedures.
- **Laboratory and R&D Analysis** - Rheology, product research and development specifications.
- **Preventive Maintenance** - Oven, Fryer, smoker and cooker adjustment. Top vs. bottom differential, and lateral heat dispersion.
- **Sales & Marketing** - Establishes customer specifications and settles customer complaints.
- **Training** - Trains employees to assess color quality in minutes, with high degrees of accuracy.



Simple Operation

Fast, easy, and accurate for production-level environments. Even first-time users can operate the BC-10 quickly and easily.

1. Switch on the power.
2. Perform white tile calibration.
3. Place on product and press button.
4. Measurement results are displayed immediately.

Display Examples

BAKING CONTRAST UNITS (BCU)

DATA 1	BCU 3.35
--------	----------

A Baking Contrast Unit is the measure of the lightness or darkness of a product. Developed specifically for the food industry, BCU is a derivative of the "L" value in standard tristimulus colorimetry. BCUs range from 0 for the darkest to 5.25 for the lightest. Each change of 0.1 BCU equals approximately on discernible shade to the human eye.

AVERAGING FUNCTION

DATA 7	AVE 3.05
MAX 3.33	MIN 2.59

The BC-10 takes as many measurements as required, and can store up to 16 readings at a time. To display the average of the stored readings, simply press the Average Button.

Rugged and lightweight

The durable BC-10 is compact, lightweight, and fits comfortably in your hand. It is battery powered for optimum convenience - you can take the product to the meter or bring the meter to the product. Includes wrist strap for added security.



Optional RS-232 Output Cable enables continuous ASCII output of measurement data to a printer, computer, or storage device.



Two measuring modes: BCU and L*a*b*
Uses four AA-size batteries or optional AC Adapter.

Specifications

Illuminating/viewing system	8/d (8" illumination/diffuse viewing)
Measuring Area	8mm round
Display Modes	0.01 - 5.25 BCU (Baking Contrast Units) & L*a*b*
Repeatability	Standard deviation within E*ab 0.1 (Measurement conditions: average of measurements of standard white plate)
Statistical Capability	Minimum, Maximum, and Mean Computation on last 16 measurements
Data Output	RS-232C ASCII data output stream Δ
Minimum interval between measurements	0.7 seconds initial, 0.4 seconds continuous
Power Source	Four AA-size batteries or optional AC adapter
Operating temperature range	-20 to 40°C (-4 to 104°F) no condensation
Size	59 x 159 x 85mm (2 1/4 x 3 1/4 x 6 1/4 in.)
Weight	370g (12.7 oz.) not including batteries
Standard Accessories	Soft Case CR-A68, Wrist Strap CR-A73, Protective Cap CR-A72, Measurement Window Cap w/ 2 windows, Instructional Videotape, Four AA Batteries
Optional Accessories	AC-A12 AC Adapter, RS-232 cable, Mini-Printer, Value Plus Warranty Program



Certificate No: YKA 0937154
Registration Date: March 3, 1995



Certificate No: JQA-E-80027
Registration Date: March 12, 1997



SAFETY PRECAUTIONS

For correct use and for your safety, be sure to read the instruction manual before using the instrument.
• Always connect the instrument to the specified power supply voltage. Improper connection may cause a fire or electric shock.

The specifications and drawings given here are subject to change without prior notice.
- If you have any questions about the specifications, please contact your Konica Minolta representative.

Konica Minolta Sensing, Inc.
Konica Minolta Sensing Americas, Inc.

Osaka, Japan
New Jersey, U.S.A.

Konica Minolta Sensing Europe B.V.

European Headquarter/BENELUX
German Office
French Office
UK Office
Italian Office
Belgian Office
Swiss Office
Nordic Office
Austrian Office
Polish Office
SE Sales Division
SE Beijing Office
SE Guangzhou Office
Singapore
Seoul Office

Nieuwegein, The Netherlands
München, Germany
Roissy CDG, France
Milton Keynes, United Kingdom
Milan, Italy
Zaventem, Belgium
Dietikon, Switzerland
Västra Frölunda, Sweden
Wien, Austria
Wroclaw, Poland
Shanghai, China
Beijing, China
Guangzhou, China
Seoul, Korea

Phone: 888-473-2656 (in USA),
201-236-4300 (outside USA)
Phone: +31(0)30 248-1193
Phone: +49(0)89 4357 156 0
Phone: +33(0)1 493-82519
Phone: +44(0)1908 540-622
Phone: +39 02 39011.425
Phone: +32 (0)2 7170 933
Phone: +41(0)43 322-9800
Phone: +46(0)31 7099464
Phone: +43(0)1 87882-430
Phone: +48(0)71 330 50 01
Phone: +86-021-5489 0202
Phone: +86-010-8522 1551
Phone: +86-020-3826 4220
Phone: +65 6563-5533
Phone: +82(0)2-523-9726

Fax: 201-785-2480
Fax: +31(0)30 248-1280
Fax: +49(0)89 4357 156 99
Fax: +33(0)1 493-84771
Fax: +44(0)1908 540-629
Fax: +39 02 39011.223
Fax: +32 (0)2 7170 977
Fax: +41(0)43 322-9809
Fax: +46(0)31 474945
Fax: +43(0)1 87882-431
Fax: +48(0)71 734 52 10
Fax: +86 -021-5489 0005
Fax: +86-010-8522 1241
Fax: +86-020-3826 4223
Fax: +65 6560-9721
Fax: +82(0)2-523-9729

Konica Minolta (CHINA) Investment Ltd.
Konica Minolta Sensing Singapore Pte Ltd.
Konica Minolta Sensing, Inc.